

## Thermal imager

**testo 865 –  
Switch on, aim, know more.**

---

Infrared resolution 160 x 120 pixels

---

With testo SuperResolution to 320 x 240 pixels

---

Automatic recognition of hot-cold spots

---



The thermal imager testo 865 is the ideal entry into the world of thermography. It stands out thanks to the best image quality in its class and handy operation, is robust enough to withstand tough daily use, and has useful functions for even better thermal images.

And all this at a ground-breaking price-performance ratio. Switch on, aim, know more.

# Ordering data

## testo 865

Thermal imager testo 865 with USB cable, mains unit, Lithium ion rechargeable battery, pro software, quick-start guide, short instructions, calibration protocol\* and case

\*calibration certificate (optional) (on extra charges)

Order no. 0560 8650



Accessories	Order no.
Spare battery, additional Lithium ion rechargeable battery for extending the operating time.	0515 5107
Battery charger, desktop charging station for optimizing the charge time.	0554 1103
Emissivity tape, adhesive tape e.g. for bare surfaces (roll, L.: 10 m, W.: 25 mm), ε = 0.95, temperature-proof up to +250 °C.	0554 0051
Holster case	0554 7808
PC software testo IRSofT for data analysis and reporting	0501 8809

# Technical data

Infrared image output	
Infrared resolution	160 x 120 pixels
Thermal sensitivity (NETD)	120 mK
Field of view/min. focusing distance	31° x 23° / < 0.5 m
Geometric resolution (IFOV)	3.4 mrad
testo SuperResolution (Pixel/IFOV)	320 x 240 pixels / 2.1 mrad
Image refresh rate	9 Hz
Focus	Auto focus
Spectral range	7.5 to 14 μm
Image presentation	
Image display	8.9 cm (3.5") TFT, QVGA (320 x 240 pixels)
Display options	IR image
Colour palettes	iron, rainbow HC, cold-hot, grey
Data interfaces	
USB 2.0 Micro B	✓
Measurement	
Measuring range	-20 to +280 °C
Accuracy	±2 °C, ±2 % of measured value
Emissivity / reflected temperature compensation	0.01 to 1 / manual
Measurement functions	
Analysis functions	Mean point measurement, hot/cold-spot recognition, Delta T,
testo ScaleAssist	✓
IFOV warner	✓

Imager equipment	
Lens	31° x 23°
Video streaming	via USB
Storage as JPG	✓
Fullscreen mode	✓
Image storage	
File format	.bmt and .jpg; export options in .bmp, .jpg, .png, .csv, .xls
Memory	Internal memory (2.8 GB)
Power supply	
Battery type	Li-ion battery can be changed on-site
Operating time	4 hours
Charging options	In instrument/in charging station (optional)
Mains operation	✓
Ambient conditions	
Operating temperature range	-15 to +50 °C
Storage temperature range	-30 to +60 °C
Air humidity	10 to 90 %RH, not condensing
Housing protection class (IEC 60529)	IP54
Vibration (IEC 60068-2-6)	2G
Physical features	
Weight	510 g
Dimensions (LxWxH)	219 x 96 x 95 mm
Housing	PC - ABS
PC software	
System requirements	Windows 10, Windows 8, Windows 7
Standards, tests, warranty	
EU directive	2014/30/EU
Warranty	2 years

1981 4024/msp/1/08.2020

Subject to change without notice.

